



ACS SPINNER KIT ORDER FORM

Please furnish the following information so that we may provide the proper spinner kit for your combination of prop hub thickness, prop bolt and prop bushing diameters, and bolt hole pattern.

All dimensions to be furnished in inches only.

1. SPINNER MODEL: _____

2. SPECIFY SAE PATTERN

SAE #1 (4-3/8), SAE #2 (4-3/4), OR SAE #3 (5-1/4): _____

3. NON STANDARD DRILLING PATTERNS: YES NO

- (\$25 charge: 4" bolt circle diameter with 6 bolts (drilled to your diameter bolts and bushings);.....
- Rotax bolt pattern #1: 75mm bolt circle diameter with 6 holes drilled to 1/4" and 1" center hole;.....
- Rotax bolt pattern #2: 100mm bolt circle diameter with 6 holes drilled to 5/16" and 1" center hole.....

(A blank bulkhead will be supplied for any other bolt pattern not listed above for customer to drill.)

4. PROP HUB THICKNESS: _____


5. PROP BOLT SIZE (DIAMETER): _____

6. PROP BOLT BUSHING DIAMETER: _____


7. FORWARD FACING FLANGE: 05-00585..... YES NO
(\$60 Charge for Forward Facing Flange)

ACS machine fee PN# 05-04904 \$25.00

REGULAR FLANGE



FORWARD FACING FLANGE



(Standard dome will need to be trimmed which causes the dome to be slightly shorter and have a smaller diameter)

8. HIGH POLISH..... YES NO
(\$60 Charge for high Polish Spinner)

9. STANDARD CENTER HOLE ON REAR BULKHEAD? YES NO
(\$60 Charge for a Non-Standard Center Hole)

Standard Center Holes: * Only available with a standard center hole.

- BN3: 2-5/8" SN4: 2-1/4"
- AC1*: 2-5/8" SN2: 2-1/4"
- SN5: 2-5/8" BN1: 2.68"
- BN2: 2-5/8"