

CYCLO TOOLMAKERS, INC.

Material Safety Data Sheet

SECTION I

Manufacturer's Name: Cyclo Toolmakers, Inc

Address: 1740 Skyway Drive, Longmont, CO 80504

Telephone: (303) 485- 1990

Date Prepared: December 22, 2004

Product Name: **CTI PRO PAINT CARE, CLEANER-DEOXIDIZER (84-151, 84-156)**

CHEM-TEL (800) 255-3924 CHEMICAL EMERGENCY CONTACT

SECTION II: Hazardous Ingredients/Identity Information

| Hazardous Components | CAS# | OSHA PEL | ACGIH TLV | Other |
|----------------------|------------|------------------------------|-----------------------------|-------|
| Solvent Naptha | 64742-94-5 | 400 ppm (TWA) | | |
| Naphthalene | 91-20-3 | 10 ppm (TWA) 15 ppm(STEL) | 10 ppm(TWA) 15 ppm(STEL) | |

SECTION III: Physical/Chemical Characteristics

Boiling Point: Approximately 195°F

Specific Gravity: 0.919

Vapor Pressure: NA

Melting Point: NA

Vapor Density: Heavier than air

Evaporation Rate: Slower than ether

Solubility in water: Complete

Appearance and Odor: Thick yellow liquid with mild solvent odor.

SECTION IV: Fire and Explosion Hazard Data

Flash Point: 102° F (tag closed cup)

Flammable Limits: N/A

LEL: NI

UEL: NI

Extinguishing Media: Carbon dioxide, dry chemical, foam or water.

Class A, BC or ABC fire extinguisher.

Special Fire Fighting Procedures: Water can be used to cool containers adjacent to fire.

Self-contained breathing apparatus should be worn.

Unusual Fire and Explosion Hazards: Pressure may develop in closed containers if temperatures over 195°F are achieved. Avoid use around sparks and open flames, vapor may travel to ignition source.

SECTION V

Stability: Stable

Conditions to Avoid: NA

Incompatibility: Strong acids, strong alkalis and strong oxidizing agents.

Hazardous Decomposition or Byproducts: Carbon monoxide, carbon dioxide, smoke.

Hazardous Polymerization: Will not occur.

Conditions to Avoid: NA

SECTION VI: Health Hazard Data

Effects of Overexposure

Routes of Entry: Eye contact, Skin contact, Inhalation and ingestion

Eyes: Contact will be painful and irritating

Skin: Prolonged contact may cause irritation

Inhalation: May irritate nose, throat and chest

Emergency and First Aid Procedures

Eyes: Flush with water for 15 minutes if irritation persists, get medical attention.

Skin: Remove any contaminated clothing, clean before re-use. Flush effected area with large amounts of water.

Inhalation: Remove to fresh air. If victim is not breathing, administer artificial respiration. If any symptoms persist, contact a physician immediately.

Ingestion: If swallowed, **DO NOT** induce vomiting. Get prompt medical attention.

SECTION VII: Precautions for Safe Handling and Use

Steps to Be Taken in Case Material Is Released or Spilled: For minor spills soak up with sweeping compound or sand and transfer to a disposal container.

Waste Disposal Method: Use methods which meet all federal, state and local regulations.

Precautions to Be Taken in Handling and Storing: Storage between 40°F and 100°F is recommended. Store away from sparks and open flames.

Other Precautions: Do not take internally or inhale vapors. Avoid eye contact.

| |
|--------------------------------------|
| SECTION VIII: Control Measure |
|--------------------------------------|

Respiratory: Not normally needed.

Ventilation:

Local Exhaust: Preferable.

Mechanical (General): Acceptable

Protective Gloves: Rubber gloves.

Eye Protection: Chemical safety goggles

Other Protective Clothing or Equipment: Usually not needed.

NA – Not Applicable

NI – No Information