RIOR

WHE	LEN		FERI	OR 8
desig an on	ce original e ned for pass /off slide sw 14 28	equipment on senger conven itch. Specify v /F	A325 ML read 14 volt Piper ience and is e oltage (14V or P/N 11-03294 P/N 11-03682	aircraft. It is quipped with 28V). \$307.00 \$298.00
for re	cessed over Weight: 0.2 14	head lighting. 5 Lb. /P/l	e Model A360 Aluminum hou N 11-03685 N 11-03686	sing & Pyrex
Reco	5 RECOGNI gnition/Land (53mm) x 3. 14	r ION/LANDING ing light assem 64" (93mm) x l /P/l	LIGHT - 7168 bbly. Dimension Depth: 0.979" (N 11-11189 N 11-11190	5 Series LED ns H x W x D: 25mm) \$173.75
71144 contro tensity Only.	assembly fo olled light into control are SPECIFICA VDC • LED	eatures a posit ensity. Models which is desig TIONS: • Powe Colors: Aviatio	LED LIGHT A: ive off position including 'side ned for the S7 er Consumptio n White • Wei n	and rheostat ' mounted in- '6D. 28 VDC n: 0.06 amps
Model # Appr 7114416 - 70190R12 - 70190B12 -	ovals — 16" a — 16" a		Part / - Wht 11-077 / - Red 11-077	701 \$273.95 731 \$319.00
series ar assemblie function a ing, mode Utilizing L • Long lif	e LED (Lig es. Designed as instrumer ern alternati .ED technold e - approxir tion -compar t, no fragile fi EMI or RFI ir 1" w/o space	ht Emitting Di d to illuminate at mounting bo ve to standard ggy, the followinately 20,000 ed to alternativ lament to burn tterference Spr er • Width: 1.7	ecifications: •	nt post light at panel, and ity, long last- t post lights. s are offered: icced power s • Shock and oduces bright Wt: .03 lbs. •
Model No. W	helen P/N 0770844-00	Description 14V, 1.0" po		
7084401 01-	0770844-01	14V, 1.5" po	st 11-01216	6 \$37.65
	0770844-02 0770844-03	<u>28V, 1.0" po</u> 28V, 1.5" po		
Re	placement ligh	t hood	11-0777	5 \$0.48
instrument instrument A350 is id SPECIFIC Number A3	post light a panel and f entical to the ATIONS: • [350CN: 7011 00" (25mm) VDC, 0.08 a	Issemblies are unction as inst A350CN, but Drawing Numb	A350 and A35 designed to i rument mounti t without the cr er A350: 7011 leight: .875" (22 • Power Cons C, & 0.04 amps	Iluminate the ng bolts. The onnector nut. 6 • Drawing 2mm) without
Post Light Assem	bly`w/ nut b			
Post Light Assem		rey post	P/N 11-0117 Part No.	Price
A350CN09	Whit	e, 14 VDC	11-03205	\$38.95
A350CN10 A350CN15		, 14 VDC e, 28 VDC	11-03214 11-03210	\$36.50 \$38.95
A350CN16	Rec	. 28 VDC	11-03653	\$36.50
new Be	odel A715-1 echcraft, ar	landing light nd will retrofit	NG LIGH is standard e into older airc	quipment on raft, as well.
Accommodates PAR 36 sealed beam lamp. Order lamp separately (#4509 - 100W, 12V; #4594 or #4613 100W, 24V; Wt.				



rately (#4509 - 100W, 12V; #4594 or #4613 100W, 24V; Wt. 1/2 lb. Size: 4-3/4" dia. x 6-1/2" long x 2-1/8" deep. P/N 11-03281 \$159.75

MODEL 71141 SERIES LED LANDING LIGHT (INTER-NAL MOUNT) PAR-36 STYLE - 71141 series is a selfcontained all LED landing light assembly. The design is intended to provide a solution to the needs for a taxi & landing light on a wide variety of aircraft. All current

AIRCRAFT SPRUCE WEST

source and electronic circuitry is contained within the housing. Unit is available in several mounting configurations to retrofit existing typical PAR-36 lighting. Unit is designed to be mounted internally behind existing lens. Item ships with flying leads. Contact your OEM for installation eligibility on your aircraft. **SPECIFICATIONS:** • Power Consumption: 1.5 amps @ 28 VDC • Weight: 1.0 lbs. (454gm) • Exposed Diameter: 4.46"

(113mm). Overall • Depth: 1.90" (48mm) • Lens: Clear Polycarbonate				
Model #	Approvals	Description	Part #	Price
7114112	—	LED landing/taxing light internal mount	11-06185	\$519.00
7114122	_	LED landing/taxing light internal mount	11-06186	\$545.00



MODEL 90361 SERIES LED LANDING LIGHT (EXTERNAL MOUNT) PAR-36 STYLE - 90361 series is a self-contained all LED landing light assembly. The design is intended to provide a solution to the needs for a taxi & landing light on a wide variety of aircraft. All current source and electronic circuitry is contained within the housing. Unit is available in several mounting configu-

rations to retrofit existing typical PAR-36 lighting. Outer lens allows for mounting externally on aircraft, option of diffusion lens available upon request. Item ships with flying leads. Contact your OEM for installation eligibility on your aircraft. SPECIFICATIONS: • Power Consumption: 1.5 amps @ 28 VDC • Weight: 1.3 lbs. (590gm) • Exposed Diameter: 4.70"

		epin. 2.07 (73mm) • Lens. Clea	<u>a r oiycan</u>	JULIALE
Model #	Approvals	Description	Part #	Price
9036110		"U" bracket mounting	11-06181	\$632.00
9036115	_	LED taxi, assy with spreader optic, 14V	11-06182	\$632.00
9036120	_	"U" bracket mounting	11-06183	\$632.00
9036125	_	LED taxi, assy with spreader optic. 28V	11-06184	\$632.00

MODEL 71125 SERIES LED RECOGNITION LIGHT -71125 series LED recognition light is designed to provide supplemental lighting for a wide variety of aircraft

applications. Provides all of the advantages of LED's as a light source, no EMI/RFI, low current draw, low heat,

a light source, no Enwirth, two current draw, low near long life. Perfect for vibration prone areas. Item ships with flying leads. Several different beam spreads available. Designed to replace the Whelen A775 series. Version containing integrated MS connector also available. Can be used in conjunction with 71115 Flasher control assembly. Contact your OEM for installation eligibility on your air-craft. **SPECIFICATIONS:** • Power Consumption: 0.9 amps @ 14 Volts, 0.45 amps @ 28 Volts • Lens: Clear polycarbonate • LED Color: Aviation White • Weight: 0.3 lbs. (136gm) • Overall Width: 3.25" (83mm) Overall Depth: 1.25" (32mm) • Overall Height: 1.95" (50mm)

Depth. 1.2					
Model #	Approvals	Description	Part #	Price	
7112510		10 degree beam pattern, 14V	11-06164	\$264.95	
7112511		20 degree beam pattern, 14V	11-06165	\$292.95	
7112512		90 degree beam pattern, 14V			
7112513		30 degree beam pattern, 14V	11-07702	\$385.00	
7112520		10 degree beam pattern, 28V	11-06167	\$272.95	
7112521		20 degree beam pattern, 28V	11-06168	\$264.95	
7112522		90 degree beam pattern, 28V	11-06169	\$264.95	
7112523		30 degree beam pattern, 28V	11-07703	\$279.95	



MODEL A775 SERIES - A775 series recognition light assembly which produces up to 22,000 beam candlepower using only a 35 watt lamp. SPECIFICATIONS: • Drawing Number: 70110 • Weight: 0.14 lbs. (64gm) • Width: 3.25" (83mm) • Height: 1.75" (44mm) • Depth: 2.25" (57mm) •

Power Consumption: 2.5 amps @ 14 VDC, 1.25 amps @ 28 VDC					
Model #	Approvals	Description	Part #	Price	
7011001	FAA/PMA	Molex connector (Piper), 14V	11-07704	\$63.75	
		Molex connector (Piper), 28V			
A77514		12" leads, 14 VDC	11-03741	\$44.50	
A77528		12" leads, 28 VDC	11-03742	\$48.90	



INSTALLATION CABLE KITS - Cable kits include all required connectors for hooking up the strobe light to the power supply only. Warning placards included. All cable is 16 gauge 3/C shielded. The cable diameter is .275" (7mm). Weight is .050 lbs. per linear foot. (Kits do not

nclude switches or breakers)					
Model #	Approvals	Description	Part #	Price	
HS5		5' Cable kit	11-04204	\$35.80	
HT10		10' Cable kit	11-08173	\$35.70	
HS30		30' Cable kit	11-03285	\$53.75	
HD60	_	60' Cable kit	11-02667	\$99.85	
HDT390		90' Cable kit	11-02668	\$133.75	
HT		Install kit only	11-02669	\$17.95	

REPLACEMENT CONNECTORS - Replacement connector kits and assemblies for cables

	P TOT OUDTOU			
Model #Approvals D		Description	Part #	Price
A441		3 Position male with pins kit	11-03211	\$4.95
A442		3 Position male with sockets kit	11-03212	\$4.95
A444		2 Position male with pins ass'y	11-03700	\$4.95
A446		2 Position female with sockets ass'v		
A447		4 Position male with pins	11-07706	\$5.35
A448		4 Position female with sockets	11-07707	\$4.95

CRIMP TOOL - Pin and socket crimping tool.

Model #	Approvals	Description	Part #	Price
CRIMPAV		Pin/socket crimping tool, MILBAR #25E	11-07708	\$164.75

AIRCRAFT SPRUCE EAST

CORONA, CA • (877) 4-SPRUCE PEACHTREE CITY, GA • (877) 477-7823 Prices Subject to Change Without Notice