

RAPCO,inc.**REPLACEMENT AIRCRAFT PARTS CO.***Disc X-Reference**Disc Minimum Wear Limit*

<u>OEM#</u>	<u>DISC#</u>	<u>RAPCO#</u>	<u>Min. Wear</u>	<u>Brake Series #</u>	<u>Wheel Series#</u>
164-00206	164-2 (or) -2F	RA164-00206	See Piper Manual	30-8	40-8, 40-76
164-00300	164-3	RA164-00300	0.205	30-30	40-41
164-00400	164-4	RA164-00400	0.162	30-9	40-12, 40-19
164-00500	164-5	RA164-00500	0.157	30-19, 30-40	40-57
164-00700	164-7	RA164-00700	0.345	30-21,-35,-51	40-66, 40-67
164-00806	164-8F	RA164-00806	0.334	30-28	40-40
164-00900	164-9	RA164-00900	0.227	30-1, 30-45	40-1,40-16,40-21
164-01000	164-10	RA164-01000	0.345	30-23	40-34
164-01300	164-13	RA164-01300	0.227	30-41	40-61
164-01406	164-14F	RA164-01406	0.334	30-28	40-40
164-01501	164-15A	RA164-01501	0.327	30-52	40-75
164-01506	164-15F	RA164-01506	0.327	30-52	40-75
164-01600	164-16	RA164-01600	0.157	30-40	40-79
164-01700	164-17	RA164-01700	0.167	30-9	40-78, 40-215
164-01900	164-19	RA164-01900	0.227	30-41	40-84
164-02000	164-20	RA164-02000	0.205	30-55, 30-56	40-86, 40-88
164-02201	164-22A	RA164-02201	0.345	30-23, 30-65	40-90
164-02300	164-23	RA164-02300	0.345	30-65	40-90
164-02504	164-25A	RA164-02504	0.445	30-54	40-83, 40-96
164-02505	164-25B (or) C	RA164-02505	0.445	30-54A to C	40-83
164-02601	164-26A	RA164-02601	0.205	30-63	40-97
164-02706	164-27F	RA164-02706	0.330	30-66, 30-69	40-98, 40-117
164-02707	164-27G	RA164-02707	0.340	30-66, 30-69	40-98, 40-118
164-02800	164-28	RA164-02800	0.227	30-41	40-99
164-03006	164-30F	RA164-03006	0.282	30-67, 30-89	40-101
164-03106	164-31F	RA164-03106	0.163	30-67	40-101,-196
164-03206	164-32F	RA164-03206	See Piper Manual	30-72	40-116
164-03300	164-33	RA164-03300	0.235	30-41	40-84
164-03506	164-35F	RA164-03506	0.260	30-68	40-102
164-03601	164-36A	RA164-03601	0.327	30-52	40-75
164-03906	164-39F	RA164-03906	0.600	30-106	40-106, 40-140
164-04000	164-40	RA164-04000	0.205	30-75	40-113
164-04300	164-43	RA164-04300	0.205	30-79	40-113
164-04406	164-44F	RA164-04406	0.334	30-68	40-76, 40-102
164-04800	164-48	RA164-04800	0.327	30-52	40-75
164-05001	164-50	RA164-05001	0.475	30-88	40-76
164-05500	164-55	RA164-05500	0.492	30-113	40-138
164-05700	164-57	RA164-05700	0.525	30-96	40-131
164-05806	164-58F	RA164-05806	0.395	30-98	40-133
164-06106	164-61F	RA164-06106	0.475	30-93	40-128
164-06306	164-63F	RA164-06306	0.465	30-99	40-134



Disc X-Reference
Disc Minimum Wear Limit

<u>OEM#</u>	<u>DISC#</u>	<u>RAPCO#</u>	<u>Min. Wear</u>	<u>Brake Series #</u>	<u>Wheel Series#</u>
164-06406	164-64F	RA164-06406	0.465	30-100	40-135
164-06506	164-65F	RA164-06506	0.240	30-74	40-111
164-06700	164-67	RA164-06700	0.220	30-60	40-60
164-06900	164-69	RA164-06900	0.205	30-59	40-59
164-07200	164-72	RA164-07200	0.492	30-107	40-195
164-07400	164-74	RA164-07400	0.492	30-141	40-119, 40-166
164-07500	164-75	RA164-07500	0.205	30-59	40-59
164-07700	164-77	RA164-07700	0.470	30-123	40-141, 40-162
164-07800	164-78	RA164-07800	0.450	30-127	40-142
164-07906	164-79F	RA164-07906	0.465	30-95	40-130
164-08200	164-82	RA164-08200	0.327	30-129	40-143
164-08300	164-83	RA164-08300	0.327	30-52	40-75, 40-145
164-08406	164-84F	RA164-08406	0.330	30-66	40-98
164-08500	164-85	RA164-08500	0.325	30-164	40-151
164-09100	164-91	RA164-09100	0.492	30-97	40-132
164-09900	164-99	RA164-09900	0.275	30-181	40-230
164-20206	164-202F	RA164-20206	0.334	30-28	40-40
164-20306	164-203F	RA164-20306	0.465	30-100	40-135
164-20500	164-205	RA164-20500	0.525	30-139	40-163
164-20600	164-206	RA164-20600	0.455	30-142	40-167
164-20700	164-207	RA164-20700	0.410	30-143	40-169
164-20806	164-208F	RA164-20806	0.475	30-145	40-171
164-20900	164-209	RA164-20900	0.410	30-144	40-170
164-21000	164-210	RA164-21000	0.436	30-146	40-172, 40-289
164-21100	164-211	RA164-21100	0.492	30-149	40-175
164-21200	164-212	RA164-21200	0.327	30-52	40-75
164-21600	164-216	RA164-21600	0.405	30-83	40-120
164-21900	164-219	RA164-21900	0.590	30-158	40-195
164-22000	164-220	RA164-22000	0.360	30-159	40-198
164-22201	164-222A	RA164-22201	0.537	30-163, 30-182	40-179
164-22400	164-224	RA164-22400	0.385	30-170	40-211
164-22900	164-229	RA164-22900	0.410	30-144A	40-170B
164-23000	164-230	RA164-23000	0.565	30-210	40-279
164-30195	C-30195	RA164-30195	0.190	C30018-2, -4	D30580, D30260
164-30388	C-30388	RA164-30388	0.325	C30118-5, -6	D30291-1, -5
164-30398	C-30398	RA164-30398	0.325	D30118-3, -4	D30291-2
164-30414	C-30414	RA164-30414	0.325	D30118-1,2,5,6	D30291-3
164-30440	C-30440	RA164-30440	0.190	C30018-2,-3	D30291-4
164-30615-1	C-30615-1	RA164-30615-1	0.190	C30018-5	D30500-1
164-30615-2	C-30615-2	RA164-30615-2	0.330	C30118-5	D30660-2
164-30615-3	C-30615-3	RA164-30615-3	0.330	C30118-5	D30660-3